

Features

- Suitable for receptacles or against insulated wire
- Double insulated housing for increased safety
- Audible (buzzer) and visual (LED) indicators
- Built-in flashlight
- Pocket clip
- Auto shut off
- Cat. IV 1000V safety rating
- Includes batteries

Specifications

Voltage Range:	Low Voltage Mode: 24 to 1000VAC High Voltage Mode: 90 to 1000VAC
Frequency Range:	50 to 60Hz
Built-in Flashlight:	Yes
Pocket Clip:	Yes
Alarm:	Yes (audio/visual)
Auto Shut-off:	Yes (after 5 mins)
Low Battery Indicator:	Yes
Power Supply:	2 x AAA Batteries
Overvoltage Category:	CAT. IV 1000V
Product Certifications:	CE, ETL
Operating Temperature:	32 to 104°F (0 to 40°C)
Storage Temperature:	-4 to 122°F (-20 to 50°C)
Operating Humidity Range:	0 to 80%
Maximum Operating Altitude:	6561' (2000m)
Dimensions:	5.9 x 0.9 x 0.7" (150 x 23 x 18mm)
Weight:	1.8oz (50g)



TECHNICAL DATA



Model	Description
R5110	Non-Contact Voltage Detector with Flashlight
R5110-10PK	Non-Contact Voltage Detector with Flashlight, 10-Pack