

TECHNICAL DATA

Features

- Local and remote continuity tester
- Lightweight design, connect alligator clips and the instrument suspends from wire/cable
- Visual (flashing bi-color LEDs) and audible (pulsating beeper) indicators
- Probe flashes green or red to indicate polarity
- Remote probe allows for one person operation
- Capable of sending signal on cable/wire runs up to 10,000 ft (3000m)
- Includes remote probe and battery

Specifications

Wire Verification Distance:	10,000 feet (3000 meters)
Max Test Current:	30mA
Max Test Voltage:	9V
Minimum Wire Size:	26 gage
Power Supply:	9V battery
Product Certifications:	CE
Visual Indicator:	Yes (Green and Red LEDs)
Audible Indicator:	Yes (Pulsating Beeper, approx. 85 dB)
Fuse:	0.5A/250V
Continuity Confirmation:	Equal to or less than 2.0 K Ohms
Operating Temperature:	14 to 113°F (-10 to 45°C)
Operating Humidity:	0 to 85%
Storage Temperature:	14 to 122°F (-10 to 50°C)
Dimensions:	4.5 x 3 x 1.1 " (115 x 75 x 29mm)
Weight:	3.9oz (111g)

Model	Description
R5300	Continuity Tester
CA-52A	Soft Carrying Case

