

37 degree Flare (AN/JIC) Quick-connect Adapters

Connect a male 37° flare AN/JIC fitting to a Quick-test hose without a wrench

Features

- A unique design allows connection to standard male 37° flare fitting using a pressure-assisted o-ring seal
- Pressure helps to seal the fitting better
- Stainless steel construction
- Made in USA



37 degree Flare (AN/JIC) Quick-connect Adapters

Select a model for more information

Model	Material	End 1	End 2	Check Valve	Working Pressure
QTHA-2FSF-QD	Stainless Steel	1/4" Female 37 degree (AN/JIC) Flare with Quick-Disconnect	Male Quick-test	No	5000 PSI
QTHA-2FSA-AN-QD	Stainless Steel	1/4" Female 37 degree (AN/JIC) Flare with Quick-Disconnect	Female Quick-test	No	5000 PSI
QTHA-3FSF-QD	Stainless Steel	3/8" Female 37 degree (AN/JIC) Flare	Male Quick-test	No	5000 PSI
QTHA-4FSF-QD	Stainless Steel	1/2" Female 37 degree (AN/JIC) Flare	Male Quick-test	No	5000 PSI
QTHA-5FSF-QD	Stainless Steel	5/8" Female 37 degree (AN/JIC) Flare	Male Quick-test	No	5000 PSI